


Origami wrapping patterns for non-planar unfolded forms


Manan Arya Jet Propulsion Laboratory, California Institute of Technology

Engineering Mechanics Institute Conference 2019 19 June 2019 Pasadena, California

What is an origami wrapping pattern?

- Wraps sheet-like materials around a central body
- Generally, exhibits N-fold rotational symmetry





• 1960: Huso


1961: Lanford

1974: Scheel

1992: Guest & Pellegrino

1997: Shafer & Palmer

• 2002: Nojima



W.E. Lanford, "Folding apparatus", U.S. Patent 3010372, 1961.

• 1960: Huso


1961: Lanford

1974: Scheel

1992: Guest & Pellegrino

1997: Shafer & Palmer

• 2002: Nojima



• 1960: Huso


1961: Lanford

1974: Scheel

1992: Guest & Pellegrino

1997: Shafer & Palmer

• 2002: Nojima



• 1960: Huso


1961: Lanford

1974: Scheel

1992: Guest & Pellegrino

1997: Shafer & Palmer

• 2002: Nojima



From, S. A. Zirbel *et al.*, "Accommodating Thickness in Origami-Based Deployable Arrays," *Journal of Mechanical Design*, vol. 135, no. 11, p. 111005, Oct. 2013, based on material published in R.J. Lang, Origami in Action, St. Martin's Griffin, New York, p. 149,1997.

• 1960: Huso


• 1961: Lanford

• 1974: Scheel

1992: Guest & Pellegrino

• 1997: Shafer & Palmer

• 2002: Nojima



• 1960: Huso

1961: Lanford


1974: Scheel

1992: Guest & Pellegrino

1997: Shafer & Palmer

2002: Nojima

2013: Zirbel, Lang, et al.



- Deployable solar arrays for spacecraft
 - Enable high-power solar arrays to be folded compactly for launch



- Deployable solar arrays for spacecraft
 - Enable high-power solar arrays to be folded compactly for launch




"Video file: NASA InSight Solar Array Deployment Test" https://www.youtube.com/watch?v=ZGsmfBgA9T4

- Deployable solar arrays for spacecraft
 - Enable high-power solar arrays to be folded compactly for launch




- Deployable solar arrays for spacecraft
 - Enable high-power solar arrays to be folded compactly for launch




- Deployable solar arrays for spacecraft
 - Enable high-power solar arrays to be folded compactly for launch
- Thin, planar unfolded forms require a separate structure to provide out-of-plane stiffness
 - e.g. deployable trusses, booms, masts
- Mass, complexity, volume savings if this separate structure was not needed


- Deployable solar arrays for spacecraft
 - Enable high-power solar arrays to be folded compactly for launch
- Thin, planar unfolded forms require a separate structure to provide out-of-plane stiffness
 - e.g. deployable trusses, booms, masts
- Mass, complexity, volume savings if this separate structure was not needed









- Deployable solar arrays for spacecraft
 - Enable high-power solar arrays to be folded compactly for launch
- Thin, planar unfolded forms require a separate structure to provide out-of-plane stiffness
 - e.g. deployable trusses, booms, masts
- Mass, complexity, volume savings if this separate structure was not needed
- Partially-unfolded wrapping patterns exhibit increased bending stiffness due to out-of-plane corrugations
 - Previously achieved by tension ties to prevent full unfolding
- Can an origami pattern be designed that has a non-planar corrugated form by design?





Unfolded form, isometric view







Unfolded form, isometric view












Folded form, isometric view



Folded form, top view




Folded form, isometric view




Folded form, top view

Free parameters

N	Number of sides in the central prism			
n	Number of panels in a gore			
A	Radius of central cylinder			
d	Radial spacing between successive folded layers			
z_0	Height of the first mountain node			
$mz_{target,i}$	Target heights of the unfolded mountain nodes, $i=1,2,n$			
vz _{target, i}	Target heights of the unfolded valley nodes, $i=1,2,n$			



Folded form assumptions





$$m_i = \mathbf{R}^i \begin{bmatrix} A + d(2i - 1) \\ 0 \\ m_i \cdot \mathbf{z} \end{bmatrix} \qquad v_i = \mathbf{R}^i \begin{bmatrix} A + d(2i) \\ 0 \\ 0 \end{bmatrix}$$

$$v_i = \mathbf{R}^i \begin{bmatrix} A + d(2i) \\ 0 \\ 0 \end{bmatrix}$$

Algorithm design

Generate the fold pattern from the inside out






Folded Unfolded

Algorithm design

• Assuming known m_i , v_i , find m_{i+1} , v'_{i+1} , m'_{i+1}




minimize
$$(|m'_{i+1} \cdot \mathbf{z} - mz_{\text{target}, i+1}| + |v'_{i+1} \cdot \mathbf{z} - vz_{\text{target}, i+1}|)$$
 over the variable $(m_{i+1} \cdot \mathbf{z})$ such that $\Delta_i = \Delta'_i$ for $i = 1, 2, 3, 4$

24

. . . /


Algorithm design

• Assuming known m_i , v_i , find m_{i+1} , v'_{i+1} , m'_{i+1}




```
 [m'_{i+1}, v'_{i+1}] = \text{function generateFoldedPoints}(m'_{i+1} \cdot \mathbf{z}) \\ [c] = \text{function costFunction}(m'_{i+1}, v'_{i+1}, mz_{\text{target}, i+1}, vz_{\text{target}, i+1}) \\ [(m'_{i+1} \cdot \mathbf{z})^*] = \text{minimize}(\text{costFunction}(\text{generatedFoldedPoints}(m'_{i+1} \cdot \mathbf{z}))
```

Non-planar origami wrapping zoo



Deployed stiffness

- Innermost valley and mountain nodes are fixed
- Equal vertical loads applied to outermost valley and mountain nodes




K. Liu and G. H. Paulino, "Nonlinear mechanics of non-rigid origami: an efficient computational approach," *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, vol. 473, 2017.

K. Liu and G. H. Paulino, "MERLIN: A MATLAB implementation to capture highly nonlinear behavior of non-rigid origami," in *Proceedings of the IASS Annual Symposium*, Tokyo, Japan, 2016.

Deployed stiffness


- Innermost valley and mountain nodes are fixed
- Equal vertical loads applied to outermost valley and mountain nodes



K. Liu and G. H. Paulino, "Nonlinear mechanics of non-rigid origami: an efficient computational approach," *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, vol. 473, 2017.

Deployed stiffness

- Innermost valley and mountain nodes are fixed
- Equal vertical loads applied to outermost valley and mountain nodes





K. Liu and G. H. Paulino, "Nonlinear mechanics of non-rigid origami: an efficient computational approach," *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, vol. 473, 2017.

K. Liu and G. H. Paulino, "MERLIN: A MATLAB implementation to capture highly nonlinear behavior of non-rigid origami," in *Proceedings of the IASS Annual Symposium*, Tokyo, Japan, 2016.

Solar array performance


- Using an example array (N = 7, unfolded diameter = 1.584m)
 - Collected power (at normal solar incidence) = 835 W
 - Power for an equivalent flat plate = 875 W
 - Corrugated surface collects 95% of the power from an equivalent flat plate
- Loss mechanisms for panels due to local angle-of-incidence effects
 - Geometric loss (cos(theta))
 - Reflective loss
- Can achieve specific power ~200 W/kg
 - Current state-of-the-art solar arrays have ~150 W/kg






Fabrication of physical models


- Each gore is a chain of triangles
 - Can fabricate each gore out of planar materials




Extensions

- Can achieve different folded forms
- Can apply different objective functions to obtain different unfolded forms
 - e.g. cones, parabolas, and any other surface of revolution







Conclusions

- Developed a novel origami wrapping pattern
 - Non-planar deployed forms for out-of-plane stiffness
 - Global thickness accommodation through designed spiral folded forms
- Flexible and powerful algorithm to generate target folded forms, or target unfolded forms
- Can be simply fabricated using planar materials
- Applicable to novel lightweight deployable solar array (200 W/kg, or 30% improvement over state-of-the-art)

Acknowledgments

- Dr. Jonathan Grandidier assisted with the calculation of solar array power output.
- A part of this research was funded through the internal Research and Technology Development program at JPL. This research was carried out at the Jet Propulsion Laboratory, California Institute of Technology, under a contract with the National Aeronautics and Space Administration.

References

- 1. W.E. Lanford, "Folding apparatus", U.S. Patent 3010372, 1961.
- 2. H.W. Scheel, "Space-saving storage of flexible sheets", U.S. Patent 3848821, 1974
- 3. S. D. Guest and S. Pellegrino, "Inextensional wrapping of flat membranes," in First International Seminar on Structural Morphology, September 1992, pp. 203–215.
- 4. R.J. Lang, Origami in Action, St. Martin's Griffin, New York, p. 149,1997.
- 5. T. Nojima, "Origami Modeling of Functional Structures Based on Organic Patterns," Master's thesis, Graduate School of Kyoto University, Kyoto, Japan, 2002.
- 6. S. A. Zirbel et al., "Accommodating Thickness in Origami-Based Deployable Arrays," Journal of Mechanical Design, vol. 135, no. 11, p. 111005, Oct. 2013.
- 7. N. A. Pehrson, S. P. Smith, D. C. Ames, S. P. Magleby, and M. Arya, "Self-Deployable, Self-Stiffening, and Retractable Origami-Based Arrays for Spacecraft," in AIAA Scitech 2019 Forum, San Diego, California, 2019.
- 8. K. Liu and G. H. Paulino, "Nonlinear mechanics of non-rigid origami: an efficient computational approach," Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences, vol. 473, 2017.
- 9. K. Liu and G. H. Paulino, "MERLIN: A MATLAB implementation to capture highly nonlinear behavior of non-rigid origami," in Proceedings of the IASS Annual Symposium, Tokyo, Japan, 2016.



